

IDENTITY (As used on label and list) Acrylic Floor Stripper Crete-Strip 142	Note: Blank spaces are not permitted. If any item is not applicable or no information is available, the space must be marked to indicate that.
--------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------

Section I

Manufacturer's Name: Curecrete Chemical Company	Emergency Telephone Number 1-800-255-3924 International Emergency Number (call collect) 813-248-0585
1201 W. Spring Creek Place	Information Telephone Number 1-801-489-5663
Springville, Utah 84663	Date Prepared 3-10-2002

Section II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity: Common Name(s) IARC NTP OSHA ACGIH None of components present equal to or greater than 0.1%

This mixture may irritate skin, nose and throat.

Skin contact may cause skin irritation with discomfort or rash in some individuals. Eye contact may cause eye irritation with discomfort, tearing, or blurring of vision. Inhalation may cause irritation of upper respiratory passages with sensitive persons.

Section III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	Not Applicable	Soluble in Water	Partially
Vapor Pressure	<5 mm Hg	Form	Liquid

Section IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point Method TCC	Flammable Limits 142 degrees
Extinguishing Media	Water spray, foam, dry chemical, carbon dioxide
Fire Fighting Instructions	Keep personnel removed and down wind of fire. Wear self-contained breathing apparatus. Wear full protective equipment. Cool tank/container by means of a water spray.
Unusual Fire and Explosion Hazards	Vapor, especially under warm conditions, can ignite in air. Hazardous gases and vapors that are produced in fire are carbon monoxide.

Section V - ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)	Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up.
	Use appropriate personal protective equipment during clean-up.
Initial Containment	Remove source of heat, sparks, flame, impact, friction or electricity. Dike spill. Prevent quantities of material from entering waterways, or low areas.
Spill Clean-up	Recover undamaged and minimally contaminated material for reuse and reclamation. Material can be soaked up with sawdust, sand, oil dry or other absorbent material and disposed in a land fill. Concentrate material can be washed into an approved sanitary sewer system with water. NOTE: This disposal must comply with local waste water treatment regulations.

Section VI - FIRST AID MEASURES

Route(s) of Entry:	Inhalation - If inhalation causes sensitization reactions, immediately move to fresh air. If breathing is difficult, give oxygen. Call a Physician. Normal ventilation will eliminate most problems.
Skin Contact	Skin contact will normally not cause irritation. Flush skin with water after contact. Wash contaminated clothing before reuse.
Eye Contact	Immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.
Ingesting	If swallowed, do not induce vomiting. Immediately give two glasses of water or activated charcoal slurry. Never give anything by mouth to an unconscious person. Call a physician.

* **NOTE:** To prepare activated charcoal slurry suspend 50 grams of activated charcoal in 400 ml of water and mix thoroughly. Give 5 ml/kg of body weight, or 350 ml for an average adult.

Section VII - HANDLING AND STORAGE

Handling (Personnel)	Avoid excessive breathing of vapors or mist, especially in poorly ventilated areas. Avoid excessive contact with eyes, skin, or clothing. Wash thoroughly after handling.
Storage	Do not mix with strong oxidants, acids, or alkalies. Store in a well ventilated place. Keep container tightly closed.

Section VIII - EXPOSURE CONTROLS & PERSONAL PROTECTION

Eye Face Protection	Wear safety glasses. Wear cover all chemical splash goggles when possibility exists for eye contact due to splashing or spraying of material.
Respirators	A NOSH.MSHA approved air purifying respirator with organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits in poorly ventilated areas. In most cases proper ventilation or approved face masks will be sufficient.
Protective Clothing	Wear appropriate clothing to prevent excessive contact with skin.

Section IX - STABILITY AND REACTIVITY

Incompatible With Other Materials	Strong oxidants, acids and alkalis
Decomposition	Decomposes with heat
Polymerization	Will not occur
Toxicological Information	Mild skin irritant and severe eye irritant. Components of mixture do not produce genetic damage in animals. No indication of development or reproductive effects.

Section X - TRANSPORTATION INFORMATION

Non regulated as a hazardous material by the DOT

Section XI - REGULATORY INFORMATION

Title iii Hazard Classification Sections 331 and 312

Acute	Yes
Chronic	No
Fire	No
Reactivity	No
Pressure	No
SARA Extremely Hazardous Substance	No
CERCLA Hazardous Material	No
SARA Toxic Chemical	No
CERCLA	No